## (19) World Intellectual Property Organization International Bureau

TAIPO OMPI



## (43) International Publication Date 24 February 2005 (24.02.2005)

## **PCT**

## (10) International Publication Number WO 2005/017352 A1

(51) International Patent Classification7:

F03G 7/00

(21) International Application Number:

PCT/GB2004/003450

- (22) International Filing Date: 11 August 2004 (11.08.2004)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0319042.8

13 August 2003 (13.08.2003) GF


- (71) Applicant (for all designated States except US): UNI-VERSITY OF SURREY [GB/GB]; Guildford, Surrey GU2 7XH (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): AL-MAYAHI, Abdulsalam [IQ/GB]; 11 Grafton Road, Worcester Park, Surrey KT4 7QQ (GB). SHARIF, Adel [GB/GB]; School of

Engineering, University of Surrey, Guildford, Surrey GU2 7XH (GB).

- (74) Agents: HAYES, Adrian, Chetwynd et al.; Boult Wade Tennant, Verulam Gardens, 70 Gray's Inn Road, London WC1X 8BT (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: OSMOTIC ENERGY



(57) Abstract: A process for driving a prime mover, said process comprising a) positioning a selective membrane between a liquid and a solution having a higher osmotic potential than the liquid, such that the solution becomes pressurised by the influx of liquid across the membrane, b) using the pressure generated in the solution to drive a prime mover, c) recovering the solution, d) separating at least some of the solvent from the solution to form a residual product, and e) recycling the separated solvent and/or the residual product of step d) to step a).